

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
2 September 2004 (02.09.2004)


PCT

(10) International Publication Number  
WO 2004/075567 A1

- (51) International Patent Classification: H04N 17/04
- (21) International Application Number: PCT/JP2003/007178
- (22) International Filing Date: 6 June 2003 (06.06.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 2003-45035 21 February 2003 (21.02.2003) JP
- (71) Applicant (for all designated States except US): OTSUKA ELECTRONICS CO., LTD. [JP/JP]; 26-3, Shodai-tajika 3-chome, Hirakata-shi, Osaka 573-1132 (JP).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): OKA, Koichi [JP/JP]; 9-6, Ohira 2-chome, Otsu-shi, Shiga 520-0867 (JP)
- (74) Agents: INAOKA, Kosaku et al.; c/o AI ASSOCIATION OF PATENT AND TRADEMARK ATTORNEYS, Sun Mullion NBF Tower, 21st Floor, 6-12, Minamihommachi 2-chome, Chuo-ku, Osaka-shi, Osaka 541-0054 (JP).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: MEASUREMENT SYSTEM FOR EVALUATING MOVING IMAGE QUALITY OF DISPLAYS



(57) Abstract: A system is disclosed, which comprises a rotatable mirror 2, a camera 3 for taking an image of a screen 5 through the mirror 2, a photodetector 4 having a detection range covering a part of the screen 5, and a control section 6. At a time when a measuring pattern included in a moving image displayed on the screen 5 is detected by the photodetector 4, a detection signal is outputted from the photodetector 4. Based on the detection signal, the control section triggers the mirror 2 to rotate, and after the mirror 2 starts rotating, the control section 6 controls so that the mirror 2 rotates to follow the motion of the measuring pattern. It is possible to obtain images that trace the motion of the moving image on a detector plane of the camera 3 without resorting to electrical synchronization of the rotation of the mirror and moving image signals, and to measure the moving image quality of displays with a simple structure.

WO 2004/075567 A1